



TECHNICAL DATA SHEET

LUSTER SEAL® 300

Clear Non-Yellowing Concrete Cure and Seal

03390

CONCRETE CURING
CONCRETE

1. **DESCRIPTION:** LUSTERSEAL 300 is a solvent based, clear sealer and hardener for concrete.

FEATURES AND BENEFITS

- *Non-yellowing*
- *Dustproofs, protects, decorates*
- *Reduces spalling*
- *VOC compliant*
- *Easily cleaned*
- *Abrasion resistant*
- *Complies with ASTM C1315 and ASTM C309*
- *Provides glossy, "wet" look*

APPLICATIONS

Exterior and interior horizontal and vertical surfaces such as:

- *Driveways*
- *Pavars*
- *Stamped concrete*
- *Showrooms*
- *Decorative concrete*
- *Patios*
- *Warehouse floors*
- *Garages*
- *Exposed aggregate*

2. **COMPOSITION AND MATERIALS:** LUSTER SEAL 300 is a proprietary formulation of methly methacrylate copolymer resin in a solvent blend.

MATERIAL PROPERTIES @ 75°F., 50% R.H.

Weight per gallon, lbs	7.5
Viscosity, cps	250
Tukon hardness	>10
Flash Point, F	110
ASTM C1315 test results	
Coverage rate, sq. ft./gal	300
Solids, %	>25
Dry time, hrs.	1-3
UV exposure	Meets Class A Requirements
Water loss, kg/m2	<0.35
Acid/Alkali resistance	Meets Requirements

3. **COLORS:** LUSTER SEAL 300 is available only in clear formulations.

4. **SURFACE PREPARATION: Existing Concrete:** When used as a sealer the surface must be structurally sound, free of dust, dirt, mortar residue, curing and form release compounds and all other contaminants. Prior to application, all surface defects, cracks, voids and joints

must be properly filled and allowed to cure per manufacturers recommendations. A dry substrate offers better product penetration than a damp surface. **Freshly Placed Concrete:** Horizontal surface must be finished and the surface "moisture" sheen should have disappeared. The surface must be able to withstand foot traffic from workmen. Vertical surfaces may be treated as soon as the forms have been removed and the surface rubbed.

5. **MIXING INSTRUCTIONS:** LUSTER SEAL 300 does not require mixing. Do not thin or dilute.

6. **APPLICATION TECHNIQUES:** Apply LUSTER SEAL 300 in a uniform, continuous film by airless sprayer, short napped mohair roller, lambs wool applicator, paint brush, or soft bristled push broom. **Freshly Placed Concrete:** Apply a full, even coat of LUSTER SEAL 300 to ensure complete, uniform coverage of the surface. Use a lambs wool applicator or roller to pick up puddles or excess material. A second coat may be applied if a higher gloss finish is desired. The second coat should be applied as soon as the first coat has dried. **Existing Concrete:** Apply a uniform film of LUSTER SEAL 300. Apply a second coat, if desired, as soon as the first coat has dried. Full cure will occur overnight and maximum hardness will be achieved in about one week.

7. **COVERAGE:** The following coverage rates are approximate and for estimating purposes only. Make test applications on actual surfaces to determine coverage rates.

Application	sq. ft./gal
Cure/Seal New Concrete	300-400
Seal/Dustproof Old Concrete	200-400
Anti-spalling	200-400

8. **CLEAN-UP INSTRUCTIONS:** Clean tools and equipment with aromatic 100 or xylene immediately following use. Clean drips and over spray with solvent while still wet. If not cleaned immediately, the sealer may leave a residue on painted surfaces, glass or wood.

TAMMS INDUSTRIES
NOVEMBER 2003 (Replaces 9/00)

CONCRETE CURING
CONCRETE

TAMMS INDUSTRIES
NOVEMBER 2003 (Replaces 9/00)

03390

9. **PACKAGING:** 1 gallon, 5 gallon, 55 gallon DOT containers.
Storage: 50 - 80°F (10-27°C)
Shelf Life: 2 years properly stored.

10. **CAUTIONS:** LUSTER SEAL 300 is not recommended to seal voids, cracks or for use where hydrostatic pressure is present. Do not apply to exterior surfaces if rain is expected within 12 hours after application or in direct sunlight at ambient temperatures in excess of 90°F. The sealer may darken the surface and may accentuate surface imperfections. A test application to evaluate appearance and performance is recommended. The coefficient of friction of the surface may decline with each sealer application. Do not apply to frozen or frost filled surfaces. Not recommended for asphalt surfaces. Certain water based tile adhesives may not bond to LUSTER SEAL 300. Always apply test area to confirm adhesion.

11. **ENVIRONMENTAL AND SAFETY PRECAUTIONS:** LUSTER SEAL 300 contains petroleum distillates and is combustible. Keep away from heat, sparks and open flame. Keep containers closed until ready to use. Provide adequate ventilation. To prevent vapor build up and possible explosion, open all doors and windows and provide cross ventilation. Do not smoke. Solvent vapors can cause respiratory irritation. For respiratory problems, remove person immediately to fresh air. Contact may cause skin or eye irritation. Using respiratory devices, safety goggles and impervious gloves is recommended. Wash hands thoroughly with soap and water after handling and before eating or smoking. If ingested, do not induce vomiting and call a physician immediately. For eye contact, flush immediately with water for 15 minutes and consult a physician immediately. Do not rub eyes. Protect shrubbery, plants and grass during application. Protect asphalt, rubber and plastic surfaces from spills and over spray. READ MATERIAL SAFETY DATA SHEET BEFORE USING. MATERIAL IS FOR INDUSTRIAL USE ONLY. KEEP AWAY FROM CHILDREN AND ANIMALS. EMERGENCY RESPONSE PHONE NUMBERS ARE (800) 862-2667 TAMMS OR (800) 424-9300 CHEMTREC.

12. **TECHNICAL SERVICE:** For application procedures or surface conditions not specified above, please contact:

TAMMS INDUSTRIES, INC.
3835 State Route 72, Kirkland, IL 60146
800-862-2667 FAX: 815-522-2323
www.tamms.com

WARRANTIES: Seller warrants that the Products do not infringe upon any copyright, patent, or trademark or trade secret, nor violate the proprietary information rights of any third party. Seller warrants that its Products will conform to and perform in accordance with the Products' specifications. THE FOREGOING WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. LIMITATION ON LIABILITIES: Because of the difficulty of ascertaining and measuring damages hereunder, it is agreed that, except for claims for bodily injury, Seller's liability to the Buyer or any third party, for any losses or damages, whether direct or otherwise, arising out of the purchase of Product from Seller by Buyer shall not exceed the total amount billed and billable to the Buyer for the Product hereunder. **IN NO EVENT WILL SELLER BE LIABLE FOR ANY LOSS OF PROFITS OR OTHER SPECIAL OR CONSEQUENTIAL DAMAGES, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.**