



CCW-550 PRIMER

DESCRIPTION

CCW-550 Primer is a single component, solvent-based bituminous primer especially designed to promote adhesion of the CCW-500 Hot Applied Liquid Membrane by preparing the concrete surface.

TYPICAL USES

Use on all concrete surfaces to which CCW-500 Hot Applied Membrane is to be applied.

PACKAGING

CCW-550 Primer is packaged in 5 gallon pails and 55 gallon drums.

COVERAGE

Coverage rate will vary. The following is a guide, but Carlisle Coatings & Waterproofing Incorporated can not guarantee coverage rates.

The concrete should show a deep stain as opposed to being fully colored black.

For smooth, hair broom finish, cover concrete 500 to 600 sq. ft. per gallon

For rough finish, cover concrete 400 to 500 sq. ft. per gallon

APPLICATION

CCW-550 Primer is best applied with powered airless spray equipment. CCW-550 Primer can also be applied by roller. Use a screen in the pail to roll off excess primer. Primer has a satisfactory cure when it will not transfer when touched. Prime only areas to be waterproofed the same day. Reprime if area becomes dirty or wet.

WARNINGS

Flammable liquid and vapors. Use only with adequate ventilation. Keep liquid and vapors away from open flames. Avoid contact with eyes and skin. In the event of contact, wash off immediately. Wear protective clothing, especially impervious rubber gloves and eye protection. *Refer to the MSDS for important warnings and product information.*

TYPICAL PROPERTIES

Color	Black
Weight per gallon	7.76 lbs.
VOC Content	500 g/l
Tack Free Time	1 hour @ 77°F
Flash Point	45°F
Corrosivity	None

LIMITED WARRANTY

CARLISLE COATINGS & WATERPROOFING INCORPORATED (CARLISLE) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any CARLISLE materials prove to contain manufacturing defects that substantially effect their performance, CARLISLE will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by CARLISLE with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. CARLISLE specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of CARLISLE's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the CARLISLE material in question.

