



SURE-SEAL HP SPLICE WIPES

DESCRIPTION

HP Splice Wipes are used in conjunction with Splice Cleaners or HP-250 Primer to clean and prime membrane prior to splicing or applying Lap Sealant.

INSTALLATION

Membrane Splice:

1. Unfold Splice Wipe and saturate with Splice Cleaner or HP-250 Primer.
2. Scrub the mating surface in a round circular motion (Do not wipe on!).
3. Discard used Splice Wipes approximately every 20 linear feet (6 m) of splice.

Lap Sealant Application:

1. Unfold Splice Wipe and dampen with Splice Cleaner.
2. Wipe the splice edge at least one inch in both directions before applying Lap Sealant.

CAUTIONS AND LIMITATIONS

1. Discard Splice Wipes every 20 linear feet (6 m) of splice.
2. Discard all Splice Wipes that become contaminated with In-Seam Sealant™.
3. Always wear protective gloves and glasses when applying Splice Cleaner or HP-250 Primer with HP Splice Wipes.

TECHNICAL DATA

Size:	132" X 24" (337.5 mm X 600 mm)
Packaging:	150/Carton
Weight:	5 Lbs./Carton (2.25 Kg)

LIMITED WARRANTY

CARLISLE COATINGS & WATERPROOFING INCORPORATED (CARLISLE) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any CARLISLE materials prove to contain manufacturing defects that substantially effect their performance, CARLISLE will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by CARLISLE with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. CARLISLE specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of CARLISLE'S liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the CARLISLE material in question.

