



# SURE-SEAL

## INSIDE/OUTSIDE CORNERS

### DESCRIPTION

Sure-Seal Inside/Outside Corners consist of .060" (1.5 mm) Uncured Elastoform Flashing™ with a pre-applied SecurTAPE™ providing .090 mils (2.25 mm) of total thickness. One corner can be installed as either an Inside or an Outside corner.

### INSTALLATION

See appropriate installation guide.

### PACKAGING

20/Carton

### CAUTIONS AND LIMITATIONS

1. A heat gun is required for forming outside corners in colder temperatures as outlined in the current specifications.
2. Job site storage temperatures in excess of 90°F (32°C) may affect product shelf life.

### TECHNICAL DATA

Sizes:	7" X 9" (175 mm X 230 mm)
Packaging:	20/Carton
Weight:	5 Lbs./Carton (2.25 Kg)
Color:	Black
Shelf Life:	6 Months (when stored between 60° - 80°F (15° - 26°C))

### LIMITED WARRANTY

CARLISLE COATINGS & WATERPROOFING INCORPORATED (CARLISLE) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any CARLISLE materials prove to contain manufacturing defects that substantially effect their performance, CARLISLE will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by CARLISLE with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. CARLISLE specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of CARLISLE's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the CARLISLE material in question.

